Star POS Printing Solutions

Designed with you in mind...





Mobile Printers

Fast, lightweight and small. Star's new range of wireless mobile printers provide easyto-use printing solutions for delivery receipts; field service estimates, reports, parts lists; inventory management schedules; mobile point-of-sale receipting and sales orders to name just a few applications.

SM-S200

58mm Mobile Printer with Blue Light LCD Display

Sophisticated pocket size printer capable of producing high quality output at a fast 80mm/sec. with Bluetooth and Serial connections as well as a cover open sensor and power save facility





3"

Easy Paper Loading

SM-S300

80mm Mobile Printer

Pocket size 80mm workhorse with an extended battery life of 10 hours with Bluetooth for wireless communication and Serial for printer settings and set-up



Magnetic Stripe Reader with Serial & Bluetooth



Easy Paper Loading

3" **SM-T300**

80mm rugged Mobile Printer with LCD display & WiFi version

Ultra rugged with IP54 dust / splash proof certification. Available with or without the magnetic stripe reader with Bluetooth and WiFi versions





SM-S400

Rugged Design

4"

112mm Mobile Printer

Wide, 104mm output for data filled service reports, delivery notes or law enforcement parking or motoring tickets in a compact case



Wide 112mm Paper Width



Easy Paper Loading

Options available





4-Bay Battery Charger

SM-S200 Printer Specifications

| Print Method | Direct Line Thermal Printing |
|---|--|
| Print Speed | 80mm/sec |
| Print Width | 48mm / 2" |
| Print Resolution | 203 dpi |
| Dimensions | 80.5 (W) x 113.5 (D) x 46 (H) mm |
| Weight | 232g (with battery) |
| Battery Duration | 6 hour printing (5 minute intervals) |
| AC Adaptor | 4 hours full charge time |
| Power Voltage | 7.4V |
| Paper: Media Loading Method Width Thickness / Weight Roll Diameter | Thermal Paper "Drop-In & Print" 58mm 0.06 ~ 0.07mm 39mm |
| Interface | Bluetooth (2.1), Serial |
| Print Head Reliability | 50km |
| Barcode | Code39/93/128, JAN/EAN8, JAN/EAN13, EAN128, I2/5, KAN, UPC, CODABAR, PDF417, QR Code, DATA Matrix |
| Drop Test | 1m |
| Operating System Support | Windows [®] 7 32/64 Bit, Vista 32/64 Bit, XP 32 Bit, Server 2008, 32/64 Bit, CE, StarlO SDK |
| Magnetic Stripe Reader | Standard 1&2 Track (2&3 optional) |
| Auto Power Down Mode | 1-5 minutes configurable |
| Characters per line | 42 |
| Character Support | ANK, Simplified/Traditional Chinese, Arabic, Cyrillic, Russian, Turkish, Greek, Japanese, Persian, Latin 9 and others (upon request) |
| Included | AC Charger, Battery Pack, Serial Cable, Sample Roll, Setup Sheet |
| Options | 4 Unit Battery Charger, Car Charger, Leather Case, Extra Battery Charger, Extra Battery Pack |

SM-S300 Printer Specifications

| Print Method | Direct Line Thermal Printing |
|---|--|
| Print Speed | 65mm/sec |
| Print Width | 72mm / 3" |
| Print Resolution | 203 dpi |
| Dimensions | 107.4 (W) x 88.5 (D) x 45 (H) mm |
| Weight | 269g (with battery) |
| Battery Duration | 10 hour printing (5 minute intervals) |
| AC Adaptor | 4 hours full charge time |
| Power Voltage | 7.4V |
| Paper: Media Loading Method Width Thickness / Weight Roll Diameter | Thermal Paper "Drop-In & Print" 80mm 0.06 ~ 0.07mm 38mm |
| Interface | Bluetooth (2.1), Serial |
| Print Head Reliability | 50km |
| Barcode | Code39/93/128, JAN/EAN8, JAN/EAN13, EAN128, I2/5, KAN, UPC, CODABAR, PDF417, QR Code, DATA Matrix |
| Drop Test | 0.9m |
| Operating System Support | Windows [®] 7 32/64 Bit, Vista 32/64 Bit, XP 32 Bit, Server 2008, 32/64 Bit, CE, StarlO SDK |
| Magnetic Stripe Reader | Standard 1&2 Track (2&3 optional) |
| Auto Power Down Mode | 1-5 minutes configurable |
| Characters per line | 64 |
| Character Support | ANK, Simplified/Traditional Chinese, Arabic, Cyrillic, Russian, Turkish, Greek, Japanese, Persian, Latin 9 and others (upon request) |
| Included | AC Charger, Battery Pack, Serial Cable, Sample Roll, Setup Sheet |
| Options | 4 Unit Battery Charger, Car Charger, Extra Battery Charger, Extra Battery Pack |

SM-T300 Printer Specifications

| Print Method | Direct Line Thermal Printing |
|---|--|
| | 75mm/sec |
| Print Speed | |
| Print Width | 72mm / 3" |
| Print Resolution | 203 dpi |
| Dimensions | 120 (W) x 130.5 (D) x 58.4 (H) mm |
| Weight | 422g (with battery) |
| Battery Duration | 8 hour printing (5 minute intervals) |
| AC Adaptor | 4 hours full charge time |
| Power Voltage | 7.4V |
| Paper: Media Loading Method Width Thickness / Weight Roll Diameter | Thermal Paper "Drop-In & Print" 80mm 0.06 ~ 0.07mm 50mm |
| Interface | Bluetooth & Serial / WiFi versions |
| Print Head Reliability | 50km |
| Barcode | Code39/93/128, JAN/EAN8, JAN/EAN13, EAN128, I2/5, KAN, UPC, CODABAR, PDF417, QR Code, DATA Matrix |
| Drop Test | 1.5m |
| Operating System Support | Windows [®] 7 32/64 Bit, Vista 32/64 Bit, XP 32 Bit, Server 2008, 32/64 Bit, CE, StarlO SDK |
| Magnetic Stripe Reader | Standard 1&2 Track (2&3 optional) |
| Auto Power Down Mode | 1-5 minutes configurable |
| Characters per line | 64 |
| Character Support | ANK, Simplified/Traditional Chinese, Arabic, Cyrillic, Russian, Turkish, Greek, Japanese, Persian, Latin 9 and others (upon request) |
| Included | AC Charger, Battery Pack, Serial Cable, Belt Clip, Sample Roll, Setup Sheet, IP54 Certified |
| Options | 4 Unit Battery Charger, Car Charger, Shoulder Strap, Extra Battery Charger, Extra Battery Pack |

SM-S400 Printer Specifications

| Print Method | Direct Line Thermal Printing |
|---|--|
| Print Speed | 50mm/sec |
| Print Width | 104mm / 4" |
| Print Resolution | 203 dpi |
| Dimensions | 138.4 (W) x 88.5 (D) x 45.7 (H) mm |
| Weight | 321g (with battery) |
| Battery Duration | 11 hour printing (5 minute intervals) |
| AC Adaptor | 4 hours full charge time |
| Power Voltage | 7.4V |
| Paper: Media Loading Method Width Thickness / Weight Roll Diameter | Thermal Paper "Drop-In & Print" 112mm 0.06 ~ 0.07mm 38mm |
| Interface | Bluetooth (2.1), Serial |
| Print Head Reliability | 50km |
| Barcode | Code39/93/128, JAN/EAN8, JAN/EAN13, EAN128, I2/5, KAN, UPC, CODABAR, PDF417, QR Code, DATA Matrix |
| Drop Test | 0.9m |
| Operating System Support | Windows® 7 32/64 Bit, Vista 32/64 Bit, XP 32 Bit, Server 2008, 32/64 Bit, CE, StarlO SDK |
| Magnetic Stripe Reader | Standard 1&2 Track (2&3 optional) |
| Auto Power Down Mode | 1-5 minutes configurable |
| Characters per line | 92 |
| Character Support | ANK, Simplified/Traditional Chinese, Arabic, Cyrillic, Russian, Turkish, Greek, Japanese, Persian, Latin 9 and others (upon request) |
| Included | AC Charger, Battery Pack, Serial Cable, Sample Roll, Setup Sheet |
| Options | 4 Unit Battery Charger, Car Charger, Extra Battery Charger, Extra Battery Pack |

Other Star Specialist Brochures available:

- Star Hospitality Printing Solutions
- Star Kiosk Printing Solutions
- Star Printer Mechanisms
- Star Visual Card Loyalty & Access Read / Write Systems

Telephone +44 (0)1494 471111 or visit our web site at

www.Star-EMEA.com

Star Micronics EMEA, Star House, Peregrine Business Park, Gomm Road, High Wycombe, Buckinghamshire, HP13 7DL, UK Fax: +44 (0)1494 473333 Email: sales@Star-EMEA.com

All other trademarks, where used, are acknowledged. In accordance with Star's policy of continual product development, Star Micronics Europe Ltd, reserve the right to change or amend the specification and price of its products from time to time without prior notice.

New product information can be found at **WWW.futurePRNT.com**

